

The ION Fit is part of the cost-effective, high performance POS-X ION Series. A sleek design available with an Intel® Atom™ Dual-Core or Celeron™ Quad-Core processor, combined with a solid fanless construction make the ION Fit a quality POS terminal. Powerful, yet energy-efficient, the ION Fit is the perfect choice for any application requiring a dependable and affordable solution.



## Key Features



### Processors

Available with Atom Dual-Core D2550 1.86GHz or Celeron Quad-Core J1900 2.4GHz processors



### Touchscreen

15" (381mm) 5-wire resistive touch display or 15" Zero-Bezel touchscreen technology



### Hard Drive

2.5" (64mm) 320GB HDD or 60-120GB SSD



### Built In Cable Management

Keeps cords out of sight



### Fanless

Ideal for dusty or dirty environments



### Energy Efficient

Conserving natural resources, energy and minimizing waste



### Optional Accessories

Integrated MSR, LCM customer display, 8.4" (213mm) rear LCD, 15" (381mm) rear LCD display, or Biometric reader.

## ■ POS-X Warranty

### Industry-leading Warranty Protection

- 3 year warranty
- \*2-day Advance Exchange - standard on all products
- \*Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

\*Available in USA and Canada

## ■ POS-X Service and Support

### 24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

MODELS	ION-TP3A-D	ION-TP3A-F	ION-TP3C-F
Processor	Intel Atom D2550 1.86 GHz Dual Core	Intel Celeron J1900 2.4GHz Quad-Core	
Bezel	Standard Bezel	Standard Bezel	TruFlat Bezel
Chip Set	CPU integrated graphic + NM10, 2W	Processor Integrated	
System Memory	1 x DDR3 SO-DIMM 2-4GB	1 x DDR3 SO-DIMM 4-8GB	
Hard Drive	320GB HDD or 60-120GB SSD		
Graphic Memory	DX9, Graphic core speed at 640MHz	Intel Gen7 up to 854MHz	
Electrical	65W/19V		
PORTS			
USB	4 x USB Type A (default) (USB 2.0)	6 x USB Type A (USB 3.0 / 2.0 x1, USB 2.0 x5)	
Serial	4 x RJ45 COM4 with 5V/12V	3 x RJ45 COM3 with 12V	
VGA		1	
GigaLAN (10/100/1000)		1 x RJ45	
Parallel		1	
PHYSICAL		ENVIRONMENTAL	
Housing	ABS	Operating Temperature	32°F to 95°F (0°C to 35°C)
Weight	12.27lb (5.57kg)	Humidity	20% ~ 85% non condensing
Dimensions (w/base) (WxDxH)	14.3" x 8.26" x 14.56" (364mm x 210mm x 370mm)	Warranty	3-year warranty with free *2-day Advance Exchange Service
Tilt Angle	40° ~ 90°	Certifications	FCC, CE, LVD, RoHs, NOM
Housing Color	Black	Supported OS	POS Ready7, Win 7 Pro, Win 8 Pro, Win 10 Pro, Available with no O/S
LCD Display	15" (381mm) LED LCD	OPTIONAL ACCESSORIES	
Resistive Touch	5-Wire Resistive	ION-MR3	3-track Magnetic Stripe Reader with USB interface
		ION-RD3-LCM	Integrated 2 x 20 LCM customer display
		ION-RD3-LCD8	Integrated rear display, 8.4" (213mm) LCD, VGA
		ION-RD3-LCD15A	Integrated 15" (381mm) Bezeled Rear LCD
		ION-RD3-LCD15C	Integrated 15" (381mm) TruFlat Rear LCD
		ION-BR3	ION Integrated U.are.U 4500 BIO Reader
		WARRANTY EXTENSION AND UPGRADES	
		ZWE-TPC	2-Year Warranty Extension
		ZOE-TPC3	*3-Year Overnight Exchange
		ZOE-TPC5	*5-Year Overnight Exchange

\*Available in USA and Canada



1975 Midway Lane, Suite O  
 Bellingham, WA 98226  
 sales@pos-x.com  
 360.738.8433  
 www.pos-x.com